

PRELIMINARY



119 kW (Tier 3a)

129 kW (Tier 4f)



50 t



30.4 m



MAXCAB

653E

Telescopic crawler crane

Tier 4f emission
standards

653E Advanced. The E-Series.



1978: TX10 telescopic crane

What defines the E-Series

- More than 20 years of experience in designing and manufacturing highly specialized telescopic crawler cranes
- Highest performance in all areas
- Technology that can be handled: high-quality components without complicating them
- Long product lifetime and high value retention

Your top benefits:

- 1 Green Efficiency**
Save fuel – reduce operating costs
Work quietly – protect operator and environment



- 2 Peak performance**
Robust boom system – work on an incline of up to 4°
2 equally strong crane winches – high line speeds

- 3 Maximum usability**
maXcab – work in comfort
SENCON – work program selection made easy



- 4 Flexibility in service**
Moving under load – minimal space requirements
Strong undercarriage traction – excellent all-terrain mobility

- 5 Easy transport**
Telescopic undercarriage – ready to go in no time
Ballast unloading system – short setup time

- 6 Maintenance and service made easy**
SENNEBOGEN control system – easy error diagnostics
Simple maintenance – clear labelling

- 7 Expertise and support near you**
3 production sites – 2 subsidiaries
120 sales partners – more than 300 service points



Tier 4 emission standard

- Powerful, state-of-the-art engine
- Fuel efficient
- Low emissions

653E Powerful.

Effective.

Strong telescopic boom for demanding tasks

- Full power boom
- Work on inclines of up to 4° possible*
- Telescoping under load


Large operating range

- 30.4-meter boom length
- With fly boom extendable to 36.9 m or 43.4 m

Easy and flexible work – saves time

- Precision hydraulics allow telescoping to any boom length quickly
- Intuitive joystick control
- Ready to go in no time, even with varying work heights
- Always the ideal boom length in no time at all

Unlimited telescoping from 9.4 – 30.4 m



Unique flexibility on site

- Moveable even under high loads
- Excellent maneuverability thanks to strong undercarriage traction
- Easy, inexpensive transport and short setup time thanks to self-assembly system

Telescopic undercarriage

- Maximum stability due to extremely long, telescopic crawler chassis with large outrigger area
- Low ground pressure due to wide crawler shoes, reliable stability even during dynamic tasks
- Robust tractor chassis and well sized travel drive for maximum all-terrain movement



653E Modern. Flexible.




Hoisting winches

- Two hoisting winches working side by side
- Compact machine with small rear radius

Elevating work platform*

- Unfolds to an internal size of 4 x 1.25 m
- Payloads up to 500 kg possible
- 360° endless rotation

500 kg elevating work platform*



Quiet operation


- Consistently quiet operation due to decoupled engine mounts and soundproofing
- Sound pressure level in accordance with 2000/14/EC as much as 2 dB lower than required

Straightforward engine compartment

- Service-friendly design
- Engine Tier 3a emission standards
- Engine Tier 4f emission standards incl. AdBlue supply

* Check for availability

653E Comfort redefined



Automatic climate control

- Consistently pleasant cab climate thanks to 10 evenly distributed air vents
- Central controls make operation easy

Comfortable maXcab cab

- Air-suspension comfort seat with heater
- Convenient joystick control
- Hinged front window
- Sliding door, platform in front of cab
- Color monitor for up to 4 cameras
- Cab can be tilted 15°


SENCON control system

- Clear menu control
- Individual fine-tuning, optimal machine performance
- Integrated load moment limiting with capacity utilization indicator
- Fast troubleshooting due to detailed information

653E Maintenance and service made easy

Simplest service

- Central, easily accessible lubricating strip
- Optional: central lubrication system for automatic lubrication



HydroClean*

- 3-µm microfilter for optimal protection of hydraulic components
- Cleaner hydraulic oil, extended oil service life
- With water separator



Walkways on both sides

- Platform in front of and next to cab for more safety while entering and exiting
- Platforms along left and right sides of uppercarriage for safe maintenance



Optimized for maintenance

- Fast and easy troubleshooting thanks to straightforward and clearly labeled electrical distributor
- Easy access to all service points on the machine

* Option

653E Technical data, equipment

MACHINE TYPE

Model (type) **653**

ENGINE

Model	Cummins QSB 4.5 diesel motor, 119 kW/162 hp at 2,200 rpm Tier 3a emission standard
	Cummins QSB 4.5 diesel motor, 129 kW/175 hp at 2,200 rpm Tier 4f emission standard
	Direct injection, turbo-charged, charge air cooling, reduced emissions
Cooling	Water-cooled
Diesel filter	With water separator and heating system
Air filter	Dry filter with integrated pre-separator, automatic dust discharge, main element and safety element, contamination indicator
Fuel tank	360 l
AdBlue tank	38 l
Electrical system	24 V
Batteries	2 x 155 AH battery disconnect switch
Options	<ul style="list-style-type: none"> Low-temperature package with engine pre-heating and heated diesel filter for temperatures below -20 °C Electric fuel pump

UPPERCARRIAGE

Design	Torsion-resistant box design, precision crafted, steel bushings for boom bearings. Extremely service-friendly design, longitudinal engine
Electrical system	Central electrical distributor, battery disconnect switch
Cooling system	3-circuit cooling system with high cooling capacity, electronically regulated fan drive for water, charge air and oil cooler
Safety	Rearview and right sideview cameras, LED lighting package
Options	<ul style="list-style-type: none"> Additional LED headlights Up to 2 additional cameras Anti-corrosive maritime climate varnish Low-temperature package for use at temperatures below -20 °C

Options

- Automatic central lubrication for boom pivot point, luffing cylinder, slewing ring track and winch drum bearing
- Pinion tooth lubrication for slewing ring

HYDRAULIC SYSTEM

Load sensing/LUDV hydraulic system, electrohydraulic pilot-controlled work functions, load limit sensing control	
Pump type	Swashplate-type variable-displacement piston pump, load pressure-independent flow distribution for simultaneous, independent control of work functions
Pump control	Zero-stroke control, on-demand flow control – the pumps only pump as much oil as will actually be used, pressure purging, load limit sensing control
Operating pressure	max. 330 bar
Filtration	High-performance filtration with long change interval
Hydraulic tank	500 l
Control system	Proportional, precision electrohydraulic actuation of work movements, 2 electric servo joysticks for work functions, including winch motion display via vibration transducer, additional functions via switches and pedals
Safety	Hydraulic circuits secured with safety valves Pipe fracture safety valve for luffing and telescoping cylinders
Options	<ul style="list-style-type: none"> Bio-oil – environmentally friendly SENNEBOGEN HydroClean 3-µm hydraulic microfilter Electric heater for hydraulic tank for temperatures below -20 °C

SLEWING DRIVE

Gearbox	Compact planetary gear with slant-axis hydraulic motor, integrated brake valves
Slewing gear brake	Spring-loaded disk brake, pedal for individual braking
Slewing ring	Externally geared slewing ring, sealed
Slewing speed	0 – 2 rpm, variable

653E Technical data, equipment

CAB MAXCAB

Cab type	maXcab full-size cab, 15° tiltable
Cab equipment	Sliding door, excellent ergonomics, automatic climate control, heated seat, air-suspension comfort seat, fresh air filter/circulating air filter, 12/24 V connections, SENCON, roller shade for sunroof
Options	<ul style="list-style-type: none"> Hydraulically elevating cab E270, can be elevated 2.70 m and tilted 30° Auxiliary heating system with timer Activated-carbon filter for cab Sliding window in operator door Armored-glass windshield Armored-glass sunroof Protective roof grating FOPS protective roof grating Radio with CD player

ATTACHMENTS

Design	Decades of experience, state-of-the-art computer simulation, maximum stability, longest service life, oversized, low-maintenance bearing points, sealed special bearing bushes, precision-crafted
Telescopic boom	4-piece with pulley head, continuous hydraulic telescoping from 9.4 – 30.4 m
Hoisting winch	Slant-axis hydraulic motor drive with compact planetary gear, 50 kN pulling power (4th layer), 0 – 115 m/min. cable speed, 16 mm cable diameter, 170 m cable length. Winch motion display via vibration transducers in the joysticks
Safety brake	Spring-loaded disk brake
Crane safety	Next-generation load moment monitoring, straightforward panel displaying all important data through SENCON display, lifting limit switch, cable exit protection, pressure relief valves and pipe fracture safety device with event recorder
Cylinders	Hydraulic cylinders with high-quality sealing and guide elements
Options	<ul style="list-style-type: none"> 6.5-m fly boom, tiltable (0°, 40°), extremely fast and easy setup without auxiliary devices, locked on basic boom when not in use Fly boom extension to 13 m, tiltable (0°, 40°)

Options


- Auxiliary jib, 5-t load capacity, 1-strand
- 2nd crane winch with 50 kN pulling power (4th layer), 0 – 115 m/min. cable speed, 16 mm cable diameter and 170 m cable length
- Additional load charts accepted for 2°/4° incline position
- Suitable for use as elevating work platform with up to 4 m width and 1000 kg payload
- 3-kW electrohydraulic emergency unit
- Remote radio control

UNDERCARRIAGE

Design	T41/380 crawler undercarriage with hydraulically extendable track width. Stable welded construction.
Drive	Hydraulic travel drive for each running gear side, variable displacement hydraulic travel motors
Parking brake	Spring-loaded, hydraulically ventilated disk brake
Traveling gear	700-mm 3-grouser crawler shoes, maintenance-free tractor chassis
Speed	0 – 2.9 kph
Options	Available crawler shoe types: <ul style="list-style-type: none"> 800-mm triple-bar-shoes 900-mm triple-bar-shoes 700-mm flat crawler shoes

OPERATING WEIGHT


Mass	Approx. 50,200 kg With 30.4-m telescopic boom, 13-m fly boom, 35-t hook, 700-mm 3-grouser crawler shoes, 2 hoisting winches, hydraulically telescoping undercarriage, 8.9-t ballast, 5.5-t undercarriage ballast
Note	The operating weight varies according to model type.



653E Crane equipment



30.4-m main boom (HA)



Capacity	Weight	Rope reeving and max. load capacity									
		10	9	8	7	6	5	4	3	2	1
5 t	80 kg										5,000 kg
15 t 1-pulley	190 kg								15,000 kg	10,000 kg	5,000 kg
35 t 3-pulley	260 kg				35,000 kg	30,000 kg	25,000 kg	20,000 kg	15,000 kg	10,000 kg	5,000 kg
60 t 6-pulley	540 kg	50,000 kg	45,000 kg	40,000 kg	35,000 kg	30,000 kg	25,000 kg	20,000 kg	15,000 kg	10,000 kg	5,000 kg

653E Load ratings




30.4-m main boom (HA)

	Boom length [m]																				
	9.4			12.8			16.3			19.8			23.3			26.8			30.4		
Counterweight [t]	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
Carbody counterweight [t]	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
Undercarriage track width [m]	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3
Outreach [m]																					
2.0	50,0	40,0		31,0	31,0		28,0	26,0		15,6	15,6		14,5	14,5							
3.0	45,0	40,0		31,0	31,0		25,0	24,4		15,6	15,6		14,5	14,5		12,7	12,7				
4.0	38,0	30,0	24,0	31,0	30,0	22,7	22,0	21,7	20,0	15,6	15,6	15,6	14,5	14,5	14,5	12,6	12,6	12,6	9,2	9,2	9,2
5.0	30,0	22,5	17,0	28,0	22,6	17,3	19,3	19,3	16,0	15,6	15,6	15,5	14,2	14,2	14,2	12,4	12,4	12,4	9,2	9,2	9,2
6.0	22,0	17,0	13,0	22,5	17,0	13,2	16,9	16,6	12,8	14,9	14,9	12,6	13,6	13,6	12,3	11,9	11,9	11,9	9,2	9,2	9,2
7.0				17,5	13,4	10,4	15,0	13,3	10,3	13,6	13,4	10,4	12,5	12,5	10,2	11,1	11,1	10,0	9,1	9,1	9,1
8.0				14,2	10,9	8,4	13,5	10,8	8,3	12,2	11,2	8,7	11,2	11,2	8,7	10,3	10,3	8,6	8,7	8,7	8,4
9.0				11,7	9,0	7,0	11,7	8,9	6,9	11,1	9,3	7,3	10,2	9,6	7,5	9,4	9,4	7,4	8,2	8,2	7,3
10.0							9,9	7,5	5,8	10,1	7,9	6,1	9,3	8,2	6,4	8,6	8,3	6,4	7,8	7,8	6,4
11.0							8,5	6,4	4,9	8,9	6,8	5,2	8,5	7,0	5,5	8,0	7,2	5,6	7,3	7,3	5,6
12.0							7,4	5,5	4,1	7,7	5,9	4,5	7,9	6,1	4,7	7,3	6,3	4,9	6,8	6,4	5,0
13.0							6,4	4,7	3,5	6,8	5,1	3,9	7,1	5,4	4,1	6,8	5,5	4,3	6,4	5,7	4,4
14.0										6,0	4,5	3,4	6,2	4,7	3,6	6,3	4,9	3,8	5,9	5,0	3,9
15.0										5,4	3,9	2,9	5,6	4,2	3,2	5,8	4,4	3,3	5,6	4,5	3,5
16.0										4,8	3,5	2,5	5,0	3,7	2,8	5,2	3,9	2,9	5,2	4,0	3,1
17.0													4,5	3,3	2,4	4,7	3,5	2,6	4,9	3,6	2,7
18.0													4,1	2,9	2,1	4,3	3,1	2,3	4,4	3,2	2,4
19.0													3,7	2,6	1,8	3,9	2,8	2,0	4,1	2,9	2,1
20.0													3,3	2,3	1,5	3,6	2,5	1,7	3,7	2,6	1,9
21.0																3,3	2,2	1,5	3,4	2,4	1,6
22.0																3,0	2,0	1,3	3,1	2,1	1,4
23.0																2,7	1,8	1,1	2,9	1,9	1,2
24.0																			2,6	1,7	1,1
25.0	Tab.-Nr.: 653R-75/1977/8.9+5,5/10.14 HA 0,3°																		2,4	1,5	0,9
26.0	Tab.-Nr.: 653R-75/1577/8.9+5,5/10.14 HA 0,3°																		2,2	1,3	0,7
Parts reeving	4	10	10	3	8	8	3	6	6	2	4	4	2	4	4	2	4	4	1	4	4
I	0%			50%			100%			100%			100%			100%			100%		
II	0%			0%			0%			25%			50%			75%			100%		
III	0%			0%			0%			25%			50%			75%			0%		
Reduction of load	580			420			330			270			230			200			180		

653E Crane equipment



6.5-m or 13-m fly jib (SA)



653E Load ratings



6.5-m fly jib (SA)

8.9 t	5.5 t	Telescopic boom length [m]							
		9.4		16.3		23.8		30.3	
3.8 m		0°	40°	0°	40°	0°	40°	0°	40°
Working radius [m]									
2.0	10.0								
3.0	9.9			10.0		9.9			
4.0	8.6			9.9		9.4			
5.0	7.7		4.6	9.4		9.0		4.9	
6.0	6.9		4.4	8.7	4.6	8.5		4.8	
7.0	6.3		4.2	8.0	4.5	8.0	4.4	4.8	
8.0	5.7		4.0	7.4	4.3	7.6	4.3	4.7	
9.0	5.2		3.9	6.9	4.2	7.2	4.2	4.7	4.0
10.0	4.8		3.8	6.4	4.1	6.8	4.1	4.7	4.0
11.0	4.5		3.7	6.0	4.0	6.5	4.0	4.7	3.9
12.0	4.1			5.7	3.9	6.2	3.9	4.7	3.8
13.0				5.3	3.8	5.9	3.9	4.6	3.8
14.0				5.0	3.8	5.7	3.8	4.4	3.7
15.0				4.8	3.7	5.4	3.7	4.2	3.7
16.0				4.6	3.7	5.0	3.7	4.0	3.6
17.0				4.2		4.6	3.6	3.8	3.5
18.0				4.0		4.2	3.6	3.7	3.4
19.0						3.7	3.6	3.5	3.3
20.0						3.5	3.5	3.4	3.2
21.0						3.2	3.3	3.2	3.1
22.0						2.9		3.0	3.0
23.0						2.6		2.7	2.8
24.0						2.4		2.4	2.6
25.0								2.2	2.4
26.0								2.0	2.2
27.0								1.8	2.0
28.0								1.7	
29.0								1.5	
30.0								1.4	
31.0								1.2	
32.0	Table no.: 653R-75/1977/8.9 t + 5.5/10.14 SA6.5 0.3°							1.1	
33.0									
Parts reeving		2	1	2	1	2	1	2	1
I		0%		100%		100%		100%	
II		0%		0%		50%		100%	
III		0%		0%		50%		100%	

653E Load ratings



13-m fly jib (SA)

8.9 t	5.5 t	Telescopic boom length [m]							
		9.4		16.3		23.8		30.3	
3.8 m		0°	40°	0°	40°	0°	40°	0°	40°
Working radius [m]									
3.0		4.6							
4.0		4.4		4.6					
5.0		4.0		4.4		3.8			
6.0		3.7		4.1		3.7			
7.0		3.4		3.8		3.6		2.1	
8.0		3.1		3.6		3.4		2.1	
9.0		2.9		3.4		3.3		2.1	
10.0		2.7	1.8	3.2		3.1		2.1	
11.0		2.5	1.7	3.0		3.0		2.1	
12.0		2.3	1.7	2.8	1.7	2.9		2.1	
13.0		2.2	1.7	2.6	1.7	2.7	1.7	2.1	
14.0		2.0	1.6	2.5	1.7	2.6	1.6	2.1	
15.0		1.9	1.6	2.4	1.6	2.5	1.6	2.1	1.5
16.0		1.8	1.5	2.3	1.6	2.4	1.6	2.1	1.5
17.0		1.7	1.5	2.1	1.5	2.3	1.5	2.1	1.5
18.0		1.6		2.0	1.5	2.2	1.5	2.1	1.5
19.0				2.0	1.5	2.1	1.5	2.0	1.4
20.0				1.9	1.5	2.1	1.5	2.0	1.4
21.0				1.8		2.0	1.4	1.9	1.4
22.0				1.7		1.9	1.4	1.9	1.4
23.0				1.6		1.8	1.4	1.8	1.4
24.0				1.5		1.8	1.4	1.8	1.3
25.0						1.7	1.4	1.7	1.3
26.0						1.7	1.4	1.7	1.3
27.0						1.6		1.6	1.3
28.0						1.4		1.6	1.3
29.0						1.4		1.6	1.3
30.0								1.3	1.1
31.0								1.1	
32.0								0.9	
33.0	Table no.: 653R-75/1977/8.9+5.5/10.14 SA13 0.3°							0.7	
34.0								0.6	
Parts reeving		2	1	2	1	2	1	2	1
I		0%		100%		100%		100%	
II		0%		0%		50%		100%	
III		0%		0%		50%		100%	

653E Load ratings




Auxiliary jib (HA-S)

	Boom length [m]																				
	9.4			12.8			16.3			19.8			23.3			26.8			30.4		
Counterweight [t]	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9	8.9
Carbody counterweight [t]	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
Undercarriage track width [m]	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3
Working radius [m]																					
2.0	5,0	5,0		5,0	5,0		5,0	5,0		5,0	5,0		5,0								
3.0	5,0	5,0		5,0	5,0		5,0	5,0		5,0	5,0		5,0	5,0		5,0					
4.0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0		
5.0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
6.0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
7.0		5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
8.0		5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
9.0				5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
10.0				5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
11.0				5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0	5,0
12.0							5,0	5,0	4,3	5,0	5,0	4,6	5,0	5,0	4,8	5,0	5,0	5,0	5,0	5,0	5,0
13.0							5,0	4,9	3,7	5,0	5,0	4,0	5,0	5,0	4,2	5,0	5,0	4,4	5,0	5,0	4,4
14.0										5,0	4,6	3,5	5,0	4,8	3,7	5,0	5,0	3,8	5,0	5,0	4,0
15.0										5,0	4,0	3,0	5,0	4,3	3,2	5,0	4,4	3,4	4,4	4,5	3,5
16.0										4,2	3,6	2,6	4,4	3,8	2,8	4,9	4,0	3,0	4,1	4,1	3,1
17.0										3,7	3,1	2,2	3,9	3,4	2,5	4,1	3,5	2,6	3,9	3,7	2,8
18.0													3,6	3,0	2,1	3,7	3,2	2,3	3,8	3,3	2,5
19.0													3,2	2,7	1,8	3,4	2,9	2,0	3,5	3,0	2,2
20.0													2,8	2,4	1,6	3,0	2,6	1,8	3,2	2,7	1,9
21.0																2,8	2,3	1,5	2,8	2,4	1,7
22.0																2,5	2,0	1,3	2,7	2,2	1,5
23.0																2,3	1,8	1,1	2,4	1,9	1,3
24.0																2,0	1,6	0,9	2,2	1,7	1,1
25.0	Tab.-Nr.: 653R-75/1977/8.9+5.5/10.14 HA-S 0,3°																		2,0	1,5	0,9
26.0	Tab.-Nr.: 653R-75/1577/8.9+5.5/10.14 HA-S 0,3°																		1,8	1,4	0,8
Parts reeving	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
I	0%			50%			100%			100%			100%			100%			100%		
II	0%			0%			0%			25%			50%			75%			100%		
III	0%			0%			0%			25%			50%			75%			0%		
Reduction of load	580			420			330			270			230			200			180		



























653E Crane equipment



Elevating work platform type 4000/1000



653E Load capacity programs

		Main boom (HA)			Auxiliary jib (HA-S)			6.5-m fly jib (SA)			13-m fly jib (SA)		
Counterweight [t]	Carbody counterweight [t]												
		 3.8 m	 3.0 m	 2.3 m	 3.8 m	 3.0 m	 2.3 m	 3.8 m	 3.0 m	 2.3 m	 3.8 m	 3.0 m	 2.3 m
 8.9 t	 5.5 t	 360°	 360°	 360°	 360°	 360°	 360°	 360°	—	—	 360°	—	—

Note:

Optional load capacities available for 2° and 4° incline positions.



- Specified load ratings only apply when machine is level ($\pm 0.3^\circ$) and stable.
- Load ratings are in tons (t) and apply for 360 degrees.
- Load ratings are in accordance with EN 13000.
- The weight of the load handling devices (e.g., hook, cable) must be subtracted from the load ratings.
- Load ratings must be limited or reduced when conditions are unfavorable, such as soft or uneven ground, slopes, wind, lateral loads, swinging loads, jerking or sudden stopping of load, operator inexperience, driving with load.
- Permissible cable pull per strand in crane mode for cable diameter 16 mm – 5,000 kg.
- Specified load ratings are for reference only. See the tables in the operating manual for the applicable load rating.


653E Fly boom



Fly boom variants

- 6.5-m fly jib*
Max. 2-lines,
possible offset
angle $0^\circ/40^\circ$
- 13-m fly boom* with 6.5-m extension, line offset
angle $0^\circ/40^\circ$
- Auxiliary jib, 5-t load capacity, 1-line







(with 13-m fly boom, 2 hoisting winches, 8.9-t counterweight, 5.5-t undercarriage ballast and 35-t hook)




653E Transport dimensions and weights



Undercarriage ballast

2x 2,750 kg



Counterweight

7,000 kg





6.5-m fly boom

600 kg




6.5-m fly boom extension

250 kg



5-t auxiliary jib


50 kg



Work platform incl. adapter, width: 2.4 m

2,300 kg

653E



This catalog describes machine models, scope of equipment of individual models, and configuration options (standard equipment and optional equipment) of the machines delivered by SENNEBOGEN Maschinenfabrik. Machine illustrations can contain optional equipment and supplemental equipment. Actual equipment may vary depending on the country to which the machines are delivered, especially in regard to standard and optional equipment.

All product designations used may be trademarks of SENNEBOGEN Maschinenfabrik GmbH or other supplying companies, and any use by third parties for their own purposes may violate the rights of the owners.

Please contact your local SENNEBOGEN sales partner for information concerning the equipment variants offered. Requested performance characteristics are only binding if they are expressly stipulated upon conclusion of the contract. Delivery options and technical features subject to change. Errors and omissions excepted. Equipment is subject to change, and rights of advancement are reserved.

© SENNEBOGEN Maschinenfabrik GmbH, Straubing, Germany. Reproduction in whole or in part only with written consent of SENNEBOGEN Maschinenfabrik GmbH, Straubing, Germany.


SENNEBOGEN

SENNEBOGEN
Maschinenfabrik GmbH
Sennebogenstrasse 10
94315 Straubing, Germany

Tel. +49 9421 540-144/146
Fax +49 9421 43 882
marketing@sennebogen.de

Order no. / Item No. 187550
653HD-E-0415005-091610

GO FOR GREEN

 www.sennebogen.com